

# creLED



|----- 12 " or 14" -----|  
Surface Ceiling (or Wall)

Key Features:  
**SHATTERPROOF, MAY WALL MOUNT**

Standard 12" Model:	<b>DUPLEX-12-BN</b>
Standard 14" Model:	<b>DUPLEX-14-BN</b>
Available Options:	May Change <b>BN</b> (Brushed Nickel) to <b>PB</b> (Polished Brass) or <b>ORB</b> (Oil Rubbed Bronze)
Nominal Dimensions:	12.0" Diameter x 3.5" Depth ... or 14.0" Diameter x 4.0" Depth
Housing Specifications:	Uniform Brushed Nickel Finish over Code Gauge Steel
Diffuser Specifications:	Smooth Opal DURAC Shatterproof Thermoplastic, Asbestos Free, UV Stabilized
Lamp Specifications:	Dimmable LED, > 80 CRI, 27K-4K; 12" @ 15W/1100 Lumens, 14" @ 21W/1600 Lumen
Energy Efficiency:	73 (12") or 76 (14") LPW (Lumens per Watt), NYECC & NYSERDA Compliant
Mounting Type:	Surface Ceiling or Wall Mount (ADA Compliant) to Recessed Junction Box
Standards & Codes:	ETL Listed Dry or Damp Locations, NEC 1.08, NYC DOB (IBC), NJEC, Energy Star
Certifications:	Registered by Product Code, Unique ID, SKU, or Calendar Number

**Thank you for considering creLED quality light fixtures.** Due to ever-advancing technology and code updates, specifications & dimensions are subject to change without notice. **Support@creLED.com**