

# creLED



I- - - - - 11" or 14" Square - - - - -I  
Surface Ceiling (or Wall)

Key Features:  
**SHATTERPROOF, MAY WALL MOUNT**

Standard 11" Model:	<b>TILE-LITE-11-WH</b>
Standard 14" Model:	<b>TILE-LITE-14-WH</b>
Available Options:	Please Browse Through our Other Fixtures to Meet Your Project Needs
Nominal Dimensions:	11.0" Square x 3.25" Depth ... or 14.0" Square x 3.25" Depth
Housing Specifications:	Uniform White Enamel Finish over Code Gauge Steel
Diffuser Specifications:	Smooth Opal DURAC Shatterproof Thermoplastic, Asbestos Free, UV Stabilized
Lamp Specifications:	Dimmable LED, >80 CRI, 27K-4K; 11" @ 15W/1087 Lumens, 14" @ 25W/1605 Lumens
Energy Efficiency:	72 (11") or 64 (14") LPW (Lumens per Watt), NYECC & NYSERDA Compliant
Mounting Type:	Surface Ceiling or Wall Mount (ADA Compliant) to Recessed Junction Box
Standards & Codes:	UL Listed Dry or Damp Locations, NEC 1.08, NYC DOB (IBC), NJEC, Energy Star
Certifications:	Registered by Product Code, Unique ID, SKU, or Calendar Number

**Thank you for considering creLED quality light fixtures.** Due to ever-advancing technology and code updates, specifications & dimensions are subject to change without notice. **Support@creLED.com**