

creLED



2" Recessed Downlights



Key Features:
MINI APERTURE, WET RATED

Round Model:	MINI-LITE-2-WRB (White Round Baffle)
Square Model:	MINI-LITE-2-WSB (White Square Baffle)
Adjustable Model:	MINI-LITE-2-WGR (White Gimbal Ring)
Nominal Dimensions:	Trim: 2.0" ID, 3.125" OD; Housing: 12.0" L x 7.5" W x 4.5" Deep
Housing Specifications:	Code Gauge Steel; IC Rated; Air Tight (Note Shallow 4.5" Depth Inside Ceiling)
Trim Specifications:	Durable Opal Thermoplastic Construction; Non-Conductive for Added Safety
Lamp Specifications:	Dimmable LED, 8.8 Watts, 620 Lumens, >90 CRI, 2700K-4000K
Energy Efficiency:	70 LPW (Lumens per Watt), NYECC & NYSERDA Compliant
Mounting Type:	Recessed into Most Standard Acoustic Tile and Gypsum Board Ceilings
Standards & Codes:	UL Listed Dry, Damp or Wet Locations, NEC 1.08, NYC DOB (IBC), NJEC, Energy Star
Certifications:	Registered by Product Code, Unique ID, SKU, or Calendar Number

Thank you for considering **creLED** quality light fixtures. Due to ever-advancing technology and code updates, specifications & dimensions are subject to change without notice. Support@creLED.com