

# creLED



I-----19"-----I  
Surface Ceiling (or Wall)

Key Features:  
**SHATTERPROOF, HIGH OUTPUT**

Standard Model:	<b>CRE-111802LEDR-19-39L-WH</b>
Available Options:	Please Browse Through our Other Fixtures to Meet Your Project Needs
Nominal Dimensions:	19.0" Diameter x 4.0" Depth
Housing Specifications:	Uniform White Enamel Finish over Code Gauge Steel
Diffuser Specifications:	Smooth Opal DURAC Shatterproof Thermoplastic, Asbestos Free, UV Stabilized
Lamp Specifications:	Dimmable LED, 39 Watts, 4000 Lumens, > 81CRI, 2700K-4000K
Energy Efficiency:	102 LPW (Lumens per Watt), NYECC & NYSERDA Compliant
Mounting Type:	Surface Ceiling or Wall Mount (ADA Compliant) to Recessed Junction Box
Standards & Codes:	UL Listed Dry or Damp Locations, NEC 1.08, NYC DOB (IBC), NJEC, Energy Star
Certifications:	Registered by Product Code, Unique ID, SKU, or Calendar Number

**Thank you for considering creLED quality light fixtures.** Due to ever-advancing technology and code updates, specifications & dimensions are subject to change without notice. **Support@creLED.com**