creLED





4" Shallow Recessed

Key Features: **OPTIONAL EM BATTERY, CUSTOM COLORS**

Shallow Round Model:	CRE-1618024EMR-4RD-20L-WH
Shallow Square Model:	CRE-1618024EMR-4SQ-20L-WH
Available Options:	-EM for Field-Install Battery, -SWW for Square Wall Wash, -CC for Custom Color
Nominal Dimensions:	Trims: 4.0" ID, 5.75" OD; Housing: 14" L x 11.5" W x 4" Depth for Shallow Ceilings
Housing Specifications:	Heavy Code Gauge Steel, IC Rated for Insulated or Non-Insulated Ceilings
Diffuser Specifications:	Smooth Opal DURAC Shatterproof Thermoplastic, Asbestos Free, UV Stabilized
Lamp Specifications:	Dimmable LED, 20 Watts, 1350 Lumens, >85 CRI, 2700K-4000K
Energy Efficiency:	67 LPW (Lumens per Watt), NYECC & NYSERDA Compliant
Mounting Type:	Recessed Ceiling Mount for Standard Acoustic Tile or Gypsum Board Ceilings
Standards & Codes:	UL Listed Dry, Damp or Wet Locations, IC, NEC 1.08, NYC DOB (IBC), NJEC, Energy Star
Certifications:	Registered by Product Code, Unique ID, SKU, or Calendar Number