

# creLED



4" Shallow Recessed

## Key Features:

**OPTIONAL EM BATTERY, CUSTOM COLORS**

Shallow Round Model:	<b>LOW-HAT-4-RD-WH</b>
Shallow Square Model:	<b>LOW-HAT-4-SQ-WH</b>
Available Options:	<b>-EM</b> for Field-Install Battery, <b>-SWW</b> for Square Wall Wash, <b>-CC</b> for Custom Color
Nominal Dimensions:	Trims: 4.0" ID, 5.75" OD; Housing: 14" L x 11.5" W x 4" Depth for Shallow Ceilings
Housing Specifications:	Heavy Code Gauge Steel, IC Rated for Insulated or Non-Insulated Ceilings
Diffuser Specifications:	Smooth Opal DURAC Shatterproof Thermoplastic, Asbestos Free, UV Stabilized
Lamp Specifications:	Dimmable LED, 20 Watts, 1350 Lumens, >85 CRI, 2700K-4000K
Energy Efficiency:	67 LPW (Lumens per Watt), NYECC & NYSERDA Compliant
Mounting Type:	Recessed Ceiling Mount for Standard Acoustic Tile or Gypsum Board Ceilings
Standards & Codes:	UL Listed Dry, Damp or Wet Locations, IC, NEC 1.08, NYC DOB (IBC), NJEC, Energy Star
Certifications:	Registered by Product Code, Unique ID, SKU, or Calendar Number

**Thank you for considering creLED quality light fixtures.** Due to ever-advancing technology and code updates, specifications & dimensions are subject to change without notice. **Support@creLED.com**