

creLED



Key Features:
INCH-LITE, EASY TO SPECIFY

Standard Model:	INCH-LITE-ALUM-(Length)*-(Mounting)*
Available Options:	* Just Advise Run Length and Mounting (R for Recessed, S for Surface, P for Pendant)
Nominal Dimensions:	1.0" Nominal Cross Section (Dimensions in Drawing); Advise Run Length or Pattern
Housing Specifications:	Code Gauge Anodized Aluminum, May Field-Cut to Desired Length within Limits
Diffuser Specifications:	Smooth White DURAC Shatterproof Thermoplastic, Asbestos Free, UV Stabilized
Lamp Specifications:	LED, 4.5 Watts per Foot (May Double Output), 375 Lumens per Foot, >90 CRI, 3K-4K
Energy Efficiency:	83 LPW (Lumens per Watt), NYECC & NYSERDA Compliant
Mounting Type:	Recessed or Surface Ceiling or Wall, Pendant Mount (Aircraft Cable by Other)
Standards & Codes:	UL Dry or Damp (Add Suffix -WET for Wet Locations), NEC 1.08, NYC DOB (IBC), NJEC
Certifications:	Registered by Product Code, Unique ID, SKU, or Calendar Number

Thank you for considering creLED quality light fixtures. Due to ever-advancing technology and code updates, specifications & dimensions are subject to change without notice. **Support@creLED.com**