

creLED



I-----21"-----I
Surface Ceiling

Key Features:
SHATTERPROOF, OPTIONAL EM BATTERY

Standard Model:	CRE-211802660-EMR-21-39L-BN
Available Options:	Change BN (Br Nickel) to WH (White) or PB (Pol Brass); Add -EM for Battery Backup
Nominal Dimensions:	21.0" Diameter x 4.0" Depth
Housing Specifications:	Uniform Brushed Nickel Finish over Code Gauge Steel
Diffuser Specifications:	Smooth Opal KAYMAR Shatterproof Thermoplastic, Asbestos Free, UV Stabilized
Lamp Specifications:	Dimmable LED, 39 Watts, 4000 Lumens, >81 CRI, 2700K-4000K
Energy Efficiency:	102 LPW (Lumens per Watt), NYECC & NYSERDA Compliant
Mounting Type:	Surface Ceiling Mount to Recessed Junction Box
Standards & Codes:	UL Listed Dry Locations, NEC 1.08, NYC DOB (IBC), NJEC, Energy Star
Certifications:	Registered by Product Code, Unique ID, SKU, or Calendar Number

Thank you for considering creLED quality light fixtures. Due to ever-advancing technology and code updates, specifications & dimensions are subject to change without notice. **Support@creLED.com**