

creLED



Key Features:
FLATSCREEN, VARIETY OF MOUNTING

Standard 1X4 Model:	CRE-231802SCREEN-14-40L-R*
Standard 2X2 Model:	CRE-231802SCREEN-22-40L-R*
Standard 2X4 Model:	CRE-231802SCREEN-24-50L-R*
Available Options:	* Change R (Recessed) to S for Surface or P for Suspended; -EM for Battery Backup
Nominal Dimensions:	12" x 48", 24" x 24", 24" x 48" All with Only 2.0" Maximum Depth
Housing Specifications:	Uniform Baked White Enamel Finish over Code Gauge Steel
Diffuser Specifications:	Smooth Opal DURAC Thermoplastic, Asbestos Free, UV Stabilized
Lamp Specifications:	LED, >80 CRI, 3K-5K; 1X4 & 2X2 @ 40W/4134 Lumens, 2X4 @ 50W/5150 Lumens
Energy Efficiency:	103 LPW (Lumens per Watt), NYECC & NYSERDA Compliant
Standard Mounting:	Recess in Standard Acoustic Tile (Standard) or Gypsum Board (-Add Suffix -FL) Ceilings
Standards & Codes:	ETL Listed Dry or Damp Locations, NEC 1.08, NYC DOB (IBC), NJEC, DLC
Certifications:	Registered by Product Code, Unique ID, SKU, or Calendar Number

Thank you for considering creLED quality light fixtures. Due to ever-advancing technology and code updates, specifications & dimensions are subject to change without notice. **Support@creLED.com**