

# creLED



Key Features:  
**ULTRA THIN, VARIETY OF MOUNTING**

Standard 1X4 Model:	<b>FLATSCREEN-14-R*</b>
Standard 2X2 Model:	<b>FLATSCREEN-22-R*</b>
Standard 2X4 Model:	<b>FLATSCREEN-24-R*</b>
Available Options:	* Change <b>R</b> (Recessed) to <b>S</b> for Surface or <b>P</b> for Suspended; <b>-EM</b> for Battery Backup
Nominal Dimensions:	12" x 48", 24" x 24", 24" x 48" .... All with Only 2.0" Maximum Depth
Housing Specifications:	Uniform Baked White Enamel Finish over Code Gauge Steel
Diffuser Specifications:	Smooth Opal DURAC Thermoplastic, Asbestos Free, UV Stabilized
Lamp Specifications:	LED, >80 CRI, 3K-5K; 1X4 & 2X2 @ 40W/4134 Lumens, 2X4 @ 50W/5150 Lumens
Energy Efficiency:	103 LPW (Lumens per Watt), NYECC & NYSERDA Compliant
Standard Mounting:	Recess in Standard Acoustic Tile (Standard) or Gypsum Board (-Add Suffix <b>-FL</b> ) Ceilings
Standards & Codes:	ETL Listed Dry or Damp Locations, NEC 1.08, NYC DOB (IBC), NJEC, DLC
Certifications:	Registered by Product Code, Unique ID, SKU, or Calendar Number

**Thank you for considering creLED quality light fixtures.** Due to ever-advancing technology and code updates, specifications & dimensions are subject to change without notice. **Support@creLED.com**