

creLED



I-----2FT or 4FT-----I
Surface Wall (or Ceiling)

Key Features:

BI-LEVEL FOR STAIRS, ADA COMPLIANT

Standard 24" Model:	CRE-241802STAIR-24-18L-BILEVEL-EM* (Standard with Bi-level Sensor & EM Battery)
Standard 48" Model:	CRE-241802STAIR-48-34L-BILEVEL-EM* (Standard with Bi-level Sensor & EM Battery)
Available Options:	* Delete EM Suffix When no Emergency Battery Backup is Required
Nominal Dimensions:	24" or 48" Length x 4.5" Width x 3.5" Depth for ADA Compliance
Housing Specifications:	Uniform White Enamel Finish over Code Gauge Steel
Diffuser Specifications:	Smooth Opal DURAC Shatterproof Thermoplastic, Asbestos Free, UV Stabilized
Lamp Specifications:	LED, >82 CRI, 3000K-4000K; 24" @ 18W/2300 Lumens, 48" @ 34W/4400 Lumens
Energy Efficiency:	127 (24") or 129 (48") LPW (Lumens per Watt), NYECC & NYSERDA Compliant
Mounting Type:	Surface Wall Mount to Recessed J-Box Facing Stair Treads (May Ceiling Mount)
Standards & Codes:	UL Listed Dry Locations, NEC 1.08, NYC DOB (IBC), NJEC, DLC LP Source, ADA
Certifications:	Registered by Product Code, Unique ID, SKU, or Calendar Number

Thank you for considering creLED quality light fixtures. Due to ever-advancing technology and code updates, specifications & dimensions are subject to change without notice. **Support@creLED.com**