

creLED



I----- 2FT or 4FT -----I
Surface Ceiling, Wall or Stem Mount

Key Features:

VANDAL; EM & MOTION AVAILABLE

Standard 24" Model:	CRE-261802VANDL-24-18L
Standard 48" Model:	CRE-261802VANDL-48-34L
Available Options:	* Add -EM Suffix for Battery Backup; -MS100 Suffix for Full-On/Off Motion Sensor
Nominal Dimensions:	24.0" or 48.0" Length x 4.5" Width x 4.5" Depth
Housing Specifications:	Uniform White Enamel Finish over Code Gauge Steel
Diffuser Specifications:	Clear Prismatic Vandal-Resistant Thermoplastic, Asbestos Free, UV Stabilized
Lamp Specifications:	LED, >82 CRI, 3000K-4000K; 24" @ 18W/2300 Lumens, 48" @ 34W/4400 Lumens
Energy Efficiency:	127 (24") or 129 (48") LPW (Lumens per Watt), NYECC & NYSERDA Compliant
Mounting Type:	Surface Wall or Ceiling Mount to Recessed Junction Box; Stem or Chain Mount
Standards & Codes:	UL Listed Dry Locations, NEC 1.08, NYC DOB (IBC), NJEC, DLC LP Source
Certifications:	Registered by Product Code, Unique ID, SKU, or Calendar Number

Thank you for considering creLED quality light fixtures. Due to ever-advancing technology and code updates, specifications & dimensions are subject to change without notice. **Support@creLED.com**