

creLED



I- - - - 24", 36" or 48" - - - -I
Surface Ceiling or Wall

Key Features:
LOW PROFILE ALT TO RECESSED

24" Linear Model:	FLAT-LITE-24-WH
36" Linear Model:	FLAT-LITE-36-WH
48" Linear Model:	FLAT-LITE-48-WH
Available Options:	Add Suffix -REM for Remote Field-Installed Emergency Battery Backup
Nominal Dimensions:	2FT, 3FT or 4FT x 5" Wide Shallow Surface Faux Recessed Only 0.75" Depth
Housing Specifications:	Uniform Baked White Enamel Finish over Code Gauge Steel
Diffuser Specifications:	Smooth Opal DURAC Thermoplastic, Asbestos Free, UV Stabilized
Lamp Specifications:	Dimmable LED, 10 Watts/Linear Foot, 700 Lumens/Linear Foot, >90 CRI, 2700K-5000K
Energy Efficiency:	>70 LPW (Lumens per Watt), NYECC & NYSERDA Compliant
Standard Mounting:	Surface Ceiling or Wall Mount to Recessed J-Box; Alternate Design to Recessed Linear
Standards & Codes:	ETL Listed Dry or Damp Locations, NEC 1.08, NYC DOB (IBC), NJEC, Energy Star
Certifications:	Registered by Product Code, Unique ID, SKU, or Calendar Number

Thank you for considering creLED quality light fixtures. Due to ever-advancing technology and code updates, specifications & dimensions are subject to change without notice. **Support@creLED.com**