

# creLED



Key Features:  
**FOR PARKING GARAGES**

Standard 48" Model:	<b>CRE-291802PARK-48-34L</b>
Available Options:	Add Suffix <b>-EM</b> for Integral Battery Backup; Add Suffix <b>-MS50</b> for Bi-Level Sensor
Nominal Dimensions:	52.0" Long x 6.75" Wide x 4.5" High
Housing Specifications:	Gray/White Thermoplastic Body with Code Gauge Steel Electrical Compartments
Diffuser Specifications:	Clear Prismatic Trans-Apex DURAC Thermoplastic, Asbestos Free, UV Stabilized
Lamp Specifications:	LED, 34 Watts, 4400 Lumens, >82 CRI, 3000K-4000K
Energy Efficiency:	129 LPW (Lumens per Watt), NYECC & NYSERDA Compliant
Mounting Type:	Surface Ceiling or Pendant/Chain Mount; 7/8" Knockouts for Direct Conduit Entry
Standards & Codes:	UL Listed Wet Locations, NEC 1.08, NYC DOB (IBC), NJEC, IP67, DLC LP Source
Certifications:	Registered by Product Code, Unique ID, SKU, or Calendar Number

**Thank you for considering creLED quality light fixtures.** Due to ever-advancing technology and code updates, specifications & dimensions are subject to change without notice. **Support@creLED.com**