

# creLED



## Key Features:

**USA & NYC APPROVED, SHATTERPROOF**

USA/NYC 8" Recessed:	<b>CRE-311802PANEX-8R-2F-RM-BA</b>
USA/NYC 6" Recessed:	<b>CRE-311802PANEX-6R-2F-RM-BA</b>
USA/NYC 8" Surface:	<b>CRE-311802PANEX-8S-2F-RM-BA</b>
USA/NYC 6" Surface:	<b>CRE-311802PANEX-6S-2F-RM-BA</b>
Available Options:	May Change Standard Suffix <b>-BA</b> (Brushed Aluminum) to <b>-WH</b> for White Housing
Nominal Dimensions:	8R = 10" H x 17" W x 4" D; 6R = 8" x 15" x 4" D; 8S = 13" x 15" x 2"; 6S = 11" x 13" x 2"
Housing Specifications:	Uniform Brushed Nickel Finish over Code Gauge Steel; Integral Emergency Battery
Panel Specifications:	Vandal-Resistant Mylar KAYMAR; Red Letters; Universal Arrows, Double Face
Lamp Specifications:	4 Watt Edge Lit LED Lamp Module for Even Illumination per Code
Energy Efficiency:	>70 LPW (Lumens per Watt), NYECC & NYSERDA Compliant
Mounting Types:	Recessed Ceiling Mount ... or Surface Ceiling, Wall, or End Mount Designs
Standards & Codes:	UL 924 Listed, NEC, NYC DOB (6" Allowed for NYC Residential), NJEC, Energy Star
Certifications:	Registered by Product Code, Unique ID, SKU, or Calendar Number

**Thank you for considering creLED quality light fixtures.** Due to ever-advancing technology and code updates, specifications & dimensions are subject to change without notice. **Support@creLED.com**