

# creLED



## Key Features:

**USA & NYC APPROVED, VANDAL**

USA/NYC 8" Surface:	<b>CRE-321802UNIEX-8S-2F-RW-WH</b>
USA/NYC 6" Surface:	<b>CRE-321802UNIEX-6S-2F-RW-WH</b>
Available Options:	May Change Standard Suffix <b>-WH</b> (White) to <b>-BA</b> for Brushed Aluminum Finish
Nominal Dimensions:	8" Model: 15.5" W x 10.5" H x 2.0" D; 6" Model: 12.5" W x 8.0" H x 2.0" D
Housing Specifications:	White Enamel Finish over Code Gauge Steel; Integral Emergency Battery
Panel Specifications:	Vandal-Resistant KAYMAR Thermoplastic; Red Letters; Single or Double Face
Lamp Specifications:	4 Watt Edge Lit LED Lamp Module for Even Illumination per Code
Energy Efficiency:	>70 LPW (Lumens per Watt), NYECC & NYSERDA Compliant
Standard Mounting:	Surface Ceiling, Wall, or End Mount, Arrows may be Confirmed in Field for Simplicity
Standards & Codes:	UL 924 Listed, NEC, NYC DOB (6" Allowed for NYC Residential), NJEC, Energy Star
Certifications:	Registered by Product Code, Unique ID, SKU, or Calendar Number

**Thank you for considering creLED quality light fixtures.** Due to ever-advancing technology and code updates, specifications & dimensions are subject to change without notice. **Support@creLED.com**