

creLED



Key Features:

MULTI-MOUNT BUILDING FLOOD

Trapezoid Model:	CRE-401802CTV3-12-56L-BZ-SF* (Shown with Standard Pole Slipfitter)
Available Options:	Specify with any RAL Color for Custom Textured Polyester Powdercoat Finish
Nominal Dimensions:	10" Wide x 12" High x 7" Extension (Plus 8" Max Extension for Mounting Hardware)
Housing Specifications:	Uniform Textured Architectural Bronze Powdercoat Finish over Die-Cast Aluminum
Diffuser Specifications:	Clear Tempered KAYMAR Glass Lens; Dark-Sky Friendly when in Downlight Position
Lamp Specifications:	Dimmable LED, 56 Watts, 6509 Lumens, >80 CRI, 3000K-5000K
Energy Efficiency:	116 LPW (Lumens per Watt), NYECC & NYSERDA Compliant
Mounting Options:	* Change Suffix -SF to -KN (1/2" NPS Knuckle), -BR (2-Piece Swivel Bracket), -W (Wall)
Standards & Codes:	CSA Listed Wet Locations, NEC 1.08, NYC DOB (IBC), IP 65 Sealed
Certifications:	Registered by Product Code, Unique ID, SKU, or Calendar Number

Thank you for considering creLED quality light fixtures. Due to ever-advancing technology and code updates, specifications & dimensions are subject to change without notice. **Support@creLED.com**