

# creLED



Key Features:  
**FOR LOBBIES OR HI-OUTPUT, EM AVAIL.**

Nom. 4" Aperture Trim:	<b>MAXI-LED-4IN</b>
Nom. 8" Aperture Trim:	<b>MAXI-LED-8IN</b>
Available Options:	Suffix <b>-EM</b> for Field-Install Battery Backup, 90 Minutes per Emergency Egress Code
Trim OD Dimensions:	4" Aperture @ 6-1/4" OD      8" Aperture @ 8-3/4" OD
Housing Dimensions:	13-1/8" W x 12-1/4" L x 7.75" Deep (Premium Die Cast Aluminum Heat Sink)
Trim Specifications:	Self-Flanged Clear Aluminum Cone; Shatterproof Frosted DURAC Thermoplastic Lens
Lamp Specifications:	Dimmable LED >90 CRI, 4K    4" @ 28W/1700 Lumens    8" @ 52W/3500 Lumens
Energy Efficiency:	4" @ 67 LPW (Lumens per Watt)    8" @ 60 LPW    NYECC & NYSERDA Compliant
Mounting Type:	Recessed Ceiling Mount for Standard Acoustic Tile or Gypsum Board Ceilings
Standards & Codes:	UL Listed Dry, Damp, or Wet Locations; NEC 1.08, NYC DOB (IBC), NJEC, Energy Star
Certifications:	Registered by Product Code, Unique ID, SKU, or Calendar Number

**Thank you for considering creLED quality light fixtures.** Due to ever-advancing technology and code updates, specifications & dimensions are subject to change without notice. **Support@creLED.com**