

# creLED



Typical Heights 15' to 20'  
Spacing up to 45' O.C.

Fixture Model A:	<b>CRE-451802TRAD-TPT-WM-A-84L-BK*</b>
Fixture Model B:	<b>CRE-451802TRAD-TPT-WM-B-84L-BK*</b>
Add Wall Mt Bracket:	<b>WM-90</b> (10" H x 15" W; Aluminum); See "Poles & Bollards" for Post Top Versions
Available Options:	* Change <b>-BK</b> (Black) to any <b>-RAL Color</b> (or Provide Color Chip for Custom Match)
Fixture Dimensions:	16" Diameter x 40" H; (Nominal 48" H x 23" Extension with Wall Mount Bracket)
Housing Specifications:	Black Powder Coat over Die Cast Aluminum; Matching Extruded Aluminum Hood
Diffuser Specifications:	Prismatic Acrylic Shatterproof DURAC Lens; Type III Shielded Optics (Type V Available)
Lamp Specifications:	Dimmable LED, 84 Watts, 5411 Lumens, >80 CRI, 3000K-4000K
Energy Efficiency:	64 LPW (Lumens per Watt), NYECC & NYSERDA Compliant
Mounting Type:	Single Wall Mount Bracket; (Post Top Mounts Available under "Poles & Bollards")
Standards & Codes:	CSA Listed Wet Locations, NEC 1.08, NYC DOB (IBC), IP 65 Rated, IP 67 LED Array
Certifications:	Registered by Product Code, Unique ID, SKU, or Calendar Number

Thank you for considering **creLED** quality light fixtures. Due to ever-advancing technology and code updates, specifications & dimensions are subject to change without notice. **Support@creLED.com**