

creLED



Key Features:
UNIFORM LIGHT OUTPUT; SHATTERPROOF

Standard 24" Model:	EZ-COVE-24 (May Wire Together for Continuous Cove Runs)
Standard 48" Model:	EZ-COVE-48 (May Wire Together for Continuous Cove Runs)
Available Options:	* Add -EM Suffix for Battery Backup; Add -MS Suffix for Bi-Level Motion Sensor
Nominal Dimensions:	24" or 48" Length x 3.5" Width x 3.5" Depth for ADA Compliance
Housing Specifications:	Uniform White Enamel Finish over Code Gauge Steel
Diffuser Specifications:	Smooth Opal DURAC Shatterproof Thermoplastic, Asbestos Free, UV Stabilized
Lamp Specifications:	LED, >80 CRI, 3500K-5000K; 24" @ 20W/2348 Lumens, 48" @ 32W/3811 Lumens
Energy Efficiency:	117 (24") or 119 (48") LPW (Lumens per Watt), NYECC & NYSERDA Compliant
Mounting Type:	Surface Mount Inside Cove Wall or Ceiling via use of Standard Junction Box
Standards & Codes:	UL Listed Dry Locations, NEC 1.08, NYC DOB (IBC), NJEC, DLC Certified, ADA
Certifications:	Registered by Product Code, Unique ID, SKU, or Calendar Number

Thank you for considering creLED quality light fixtures. Due to ever-advancing technology and code updates, specifications & dimensions are subject to change without notice. **Support@creLED.com**