

creLED



Only
1.2" H

I----- 7.75" OD (Nominal 4" OD Lens) -----I

Key Features: **SHALLOW SURFACE CEILING LIGHT**

| | |
|--------------------------|---|
| Standard Model: | SHALLOW-LITE-7-WH |
| Available Options: | Please Browse Through our Other Fixtures to Meet Your Project Needs |
| Nominal Dimensions: | 7.75" OD x 1.2" Below Ceiling Line (LED Driver Hides Inside Junction Box) |
| Housing Specifications: | Uniform White Thermoplastic and Code Compliant Electrical Compartment |
| Diffuser Specifications: | Opal DURAC Shatterproof Thermoplastic, UV Stabilized Lens |
| Lamp Specifications: | LED Module, 12 Watts, 900 Lumens, >80 CRI, 2700K-5000K |
| Dimming Option: | Add Suffix -DIM for LED Dimming Module |
| Energy Efficiency: | 75 LPW (Lumens per Watt), NYECC & NYSERDA Compliant |
| Mounting Type: | Flush Surface Ceiling Mount to Standard 4" Recessed Junction Box |
| Standards & Codes: | ETL Listed Dry, Damp or Wet Locations, NEC 1.08, NYC DOB (IBC), NJEC, Energy Star |
| Certifications: | Registered by Product Code, Unique ID, SKU, or Calendar Number |

Thank you for considering creLED quality light fixtures. Due to ever-advancing technology and code updates, specifications & dimensions are subject to change without notice. **Support@creLED.com**