



GAS-SHIELD LED Fixture:
FOR GAS METER & BOILER ROOMS

Universal Mount 4FT:	GAS-SHIELD-4-NYC
Available Options:	Add Suffix -EM for Integral Battery Backup; Add Suffix -MS100 for Full On/Off Sensor
Nominal Dimensions:	51.0" Long x 4.5" Wide x 3.5" High
Housing Specifications:	Gray/White Heat Resistant KAYMAR Housing with NY Code Gauge Steel Components
Material Specifications:	KAYMAR polymers resistant to aqueous acids, alkalis, alcohols, and mineral oils
Diffuser Specifications:	Hi-Impact KAYMAR Thermoplastic, Stainless Steel Clamps, 100% K-Compression Seal
Lamp Specifications:	Premium LED (no Visible Pixelation), 52Watts, 6812 Lumens, >80 CRI, 4000K-5000K
Energy Efficiency:	131 LPW (Lumens per Watt), NYECC & NYSERDA Compliant, IEEE C62.41-1991
Mounting Type:	Surface Ceiling or Pendant/Chain Mount; 7/8" Knockouts for Direct Conduit Entry
Standards & Codes:	UL Wet Location, IP65, NEC 1.08, NYC DOB (IBC), NJEC, DLC Premium, RoHS, OSHA
Certifications:	Registered by Product Code, Unique ID, SKU, or Calendar Number

Thank you for considering creLED quality light fixtures. Due to ever-advancing technology and code updates, specifications & dimensions are subject to change without notice. **Support@creLED.com**